## NSN 5935-01-298-7910

Electrical Receptacle Connector - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5935-01-298-7910 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.490 inches **Overall Height:** 0.937 inches **Overall Width:** 0.937 inches **Environmental Protection:** Humidity resistant and salt water resistant and shock proof and vibration proof **Unthreaded Mounting Hole Diameter:** 0.120 inches **Center To Center Distance Between Mounting Facilities Parallel To Height:** 0.719 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.719 inches **Distance From Mounting Shoulder To Front Face:** Between 0.708 inches and 0.728 inches **Threaded Device Type:** Back shell **Mating End Quantity: Contact Position Arrangement Style:** 40471 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 and 95.0 and 145.0 and 220.0 and 255.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin Thread Length:

24

0.290 inches

Thready Qty Per Inch (tpi):

## NSN 5935-01-298-7910

Electrical Receptacle Connector - Page 2 of 3



Thread Size:
0.625 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic epoxy single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 1, cl 2 military specification single treatment response single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416 federal specification single treatment response
Shell Material Specification:
Qq-a-367 federal specification single material response
Included Contact Quantity:
2 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.010 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-83723 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unef
Specification Data:
81349-mil-c-83723/71 government specification
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

## NSN 5935-01-298-7910

Electrical Receptacle Connector - Page 3 of 3



Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.