NSN 5935-01-299-3058

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-299-3058 **Body Style:** Straight shape, flush mount **Overall Length:** 0.984 inches **Overall Height:** 1.687 inches **Overall Width:** 3.375 inches **Unthreaded Mounting Hole Diameter:** 0.144 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 0.995 inches and 1.005 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 2.870 inches and 2.880 inches **Distance From Mounting Shoulder To Front Face:** 0.078 inches **Mating End Quantity: Contact Position Arrangement Style:** 10 single mating end **Contact Removability:** Removable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

20.0 single mating end 2nd contact grouping

Polarization Method:

Contact

Shell Type:

Solid

Connector Locking Method:

Friction

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings and nickel single mating end all contact groupings and copper single mating end all contact groupings

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification 1st treatment response single mating end all contact groupings

Terminal Type:

Solder well single mating end all contact groupings

NSN 5935-01-299-3058

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.

Electrical Receptacle Connector - Page 2 of 2

