# NSN 5935-01-299-5311

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-299-5311

## Body Style:

Straight shape, internal coupling w/strain relief

#### **Body Length:**

1.812 inches

## **Overall Diameter:**

1.391 inches

## **Environmental Protection:**

Moisture resistant

#### Cable Entrance Diameter:

Between 0.600 inches and 0.635 inches

#### Mating End Quantity:

1

## **Contact Position Arrangement Style:**

18-32 single mating end

#### **Contact Removability:**

Removable single mating end single contact grouping

## Contact Maximum Ac Voltage Rating In Volts:

600.0 single mating end single contact grouping

# Contact Maximum Dc Voltage Rating In Volts:

850.0 single mating end single contact grouping

#### **Polarization Method:**

Keyway or multiple keyway

#### Insert Position In Deg:

0.0

## Shell Type:

Solid

## **Connector Locking Method:**

Bayonet latch

# Connector Cable Strain Relief Method:

Cable clamp

# **Operating Tempurature Rating:**

Between -65.0 degrees celsius and 200.0 degrees celsius

# **Terminal Location:**

Back single mating end single contact grouping

# **Contact Material:**

Copper alloy single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping

## Insert Material:

Plastic epoxy single mating end and glass fiber single mating end

# Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Electrical Plug Connector - Page 2 of 2



Terminal Type:	
	g end single contact grouping
Shell Material:	
Aluminum alloy	
Shell Surface Trea	atment:
Cadmium and nick	el
Shell Surface Trea	atment Specification:
Qq-p-416 federal s	pecification 1st treatment response and qq-n-290, class 2 federal specification 2nd treatment response
Included Contact	Quantity:
32 single mating er	nd single contact grouping
Included Contact	Туре:
Round pin single m	nating end single contact grouping
Precious Material	And Location:
Contact surfaces g	old
Precious Material	And Weight:
0.032 gold grains,	troy
Precious Material	:
Gold	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A039b0	
Mil-std (military S	tandard):
Mil-g-45204 spec.	