NSN 5935-01-299-6297

Receptacle Dummy Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-299-6297 **Overall Length:** Between 0.499 inches and 0.530 inches **Overall Height:** 1.141 inches Overall Width: **1.141** inches **Environmental Protection:** Salt water resistant and corrosion resistant and pressure proof **Unthreaded Mounting Hole Diameter:** Between 0.115 inches and 0.130 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.906 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.906 inches **Distance From Mounting Shoulder To Front Face:** Between 0.441 inches and 0.461 inches **Mating End Quantity:** 1 **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Cadmium **Shell Surface Treatment Specification:** Qq-p-416 federal specification single treatment response **Test Data Document:** 81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Specification Data:** 81349-mil-c-38999/10 government specification Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5935-01-299-6297

Receptacle Dummy Connector - Page 2 of 2



Fiig:

A039b0