## NSN 5935-01-299-6308

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-299-6308 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** Between 1.545 inches and 1.565 inches **Overall Height:** Between 1.115 inches and 1.135 inches **Overall Width:** Between 1.115 inches and 1.135 inches **Unthreaded Mounting Hole Diameter:** Between 0.123 inches and 0.138 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 0.896 inches and 0.916 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 0.896 inches and 0.916 inches **Distance From Mounting Shoulder To Front Face:** Between 1.092 inches and 1.112 inches **Threaded Device Type:** Back shell **Mating End Quantity: Contact Position Arrangement Style:** 13-35 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin **End Application:** F-16d tv-1d c Thready Qty Per Inch (tpi): 24

**Thread Size:** 

0.688 inches

## NSN 5935-01-299-6308

Electrical Receptacle Connector - Page 2 of 2



| Terminal Location:   |
|--|
| Back single mating end single contact grouping   |
| Contact Material:  |
| Copper alloy single mating end single contact grouping   |
| Contact Surface Treatment:   |
| Gold single mating end single contact grouping   |
| Contact Surface Treatment Specification:   |
| Mil-g-45204, type 2, gr c, cl 1 military specification single treatment response single mating end single contact grouping                 |
| Terminal Type:   |
| Crimp single mating end single contact grouping  |
| Contact Material Specification:  |
| Qq-c-530 federal specification single material response single mating end single contact grouping or qq-c-533 federal specification single |
| material response single mating end single contact grouping or qq-b-750 federal specification single material response single mating end   |
| single contact grouping  |
| Shell Material:  |
| Aluminum alloy   |
| Shell Surface Treatment:   |
| Cadmium  |
| Shell Surface Treatment Specification:   |
| Qq-p-416 federal specification single treatment response   |
| Included Contact Quantity:   |
| 22 single mating end single contact grouping   |
| Included Contact Type:   |
| Round socket single mating end single contact grouping   |
| Precious Material And Location:  |
| Contact surfaces gold  |
| Precious Material And Weight:  |
| 0.022 gold grains, troy  |
| Precious Material:   |
| Gold   |
| Thread Series Designator:  |
| Unef   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.