## NSN 5935-01-299-8410

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-299-8410

Body Style:
Angle shape
Overall Diameter:
0.175 inches
Body Angle In Deg:
90.0
Environmental Protection:
Corrosion resistant and vibration resistant and shock resistant and moisture resistant
Cable Entrance Diameter:
0.042 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
Rf single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
150.0 single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Friction
Connector Cable Strain Relief Method:
Crimp type
Radio Frequency Type Contact Characteristic Impedance In Ohms:
50.0 single mating end single contact grouping
End Application:
Alq-135b
Distance From Centerline To Cable End:
0.468 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic polytetrafluoroethylene single mating end
Contact Surface Treatment Specification:
Mil-g-45204 military specification 1st treatment response single mating end single contact grouping and qq-n-290 federal specification 2nd
treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

## NSN 5935-01-299-8410

Mil-std (military Standard):

Mil-g-45204 spec.

Electrical Plug Connector - Page 2 of 2



Contact Material Specification:
Qq-c-530 federal specification single material response single mating end single contact grouping
Shell Material:
Copper alloy
Shell Surface Treatment:
Tin and lead
Shell Surface Treatment Specification:
Mil-p-81728 military specification all treatment responses
Shell Material Specification:
Qq-b-626 federal specification single material response
Insert Material Specification:
Mil-p-19468 military specification single material response single mating end
Included Contact Quantity:
1 single mating end single contact grouping
Included Contact Type:
Coaxial pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.005 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
<b></b>
Demilitarization:
No
Fiig:
A039b0