

View Online at <https://aerobasegroup.com/nsn/5935-01-300-5840>

Body Style:

Right angle type

Overall Length:

6.300 inches

Overall Width:

0.580 inches

Body Height:

0.352 inches

Environmental Protection:

Humidity resistant and salt water resistant and thermal shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

Between 0.092 inches and 0.102 inches

Distance Between Mounting Facility Centers:

Between 6.095 inches and 6.105 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

300.0 single mating end single contact grouping

Polarization Method:

Guide pin/socket

Shell Type:

Solid

Connector Locking Method:

Friction

End Application:

6625-01-186-9197 test set, electronic systems

Terminal Location:

Side single mating end single contact grouping

Contact Material:

Copper alloy 360 single mating end single contact grouping or copper alloy 260 single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic polyamide single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, cl 1, gr c military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 1 federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Wire wrap single mating end single contact grouping

Contact Material Specification:

Qq-b-626 federal specification 1st material response single mating end single contact grouping or qq-b-613 federal specification 2nd material response single mating end single contact grouping

Guide Design And Location:

D shape pin right-hand at 6 oclock

Shell Material:

Aluminum alloy 6063 or aluminum alloy 6061

Shell Surface Treatment:

Anodize

Shell Surface Treatment Specification:

Mil-a-8625 military specification single treatment response

Shell Material Specification:

Qq-a-200/9b federal specification 1st material response or qq-a-200/8 federal specification 2nd material response

Insert Material Specification:

L-p-410 federal specification single material response single mating end or astm d 4066-82, type 1 assn standard single material response single mating end

Included Contact Quantity:

100 single mating end single contact grouping

Included Contact Type:

Flat pin single mating end single contact grouping

Special Features:

0.200 x 0.200 in. Insert in center of receptacle with 0.143 to 0.149 in. Diameter hole for connector locking; receptacle has total of four equal spaced mtg ears

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.100 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.