# NSN 5935-01-300-7728

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-300-7728

| Thread Class:   |
|---|
| 2a and 2b   |
| Thread Direction:   |
| Right-hand  |
| Body Style:   |
| Straight shape  |
| Overall Length:   |
| 0.880 inches  |
| Overall Height:   |
| 0.650 inches  |
| Overall Width:  |
| 0.280 inches  |
| Environmental Protection:   |
| Humidity resistant and shock resistant and thermal shock resistant and vibration resistant          |
| Threaded Device Type:   |
| Coupling facility   |
| Mating End Quantity:  |
| 1   |
| Contact Position Arrangement Style:   |
| 14 single mating end  |
| Contact Removability:   |
| Nonremovable single mating end single contact grouping  |
| Contact Maximum Current Rating In Amps:   |
| 3.0 single mating end single contact grouping   |
| Polarization Method:  |
| Jackscrew   |
| Connector Locking Method:   |
| Jackscrew-socket  |
| End Application:  |
| Alq-135b  |
| Thready Qty Per Inch (tpi):   |
| 56  |
| Thread Size:  |
| 0.086 inches  |
| Terminal Location:  |
| Back single mating end single contact grouping  |
| Contact Material:   |
| Copper alloy single mating end single contact grouping  |
| Contact Surface Treatment:  |
| Gold single mating end single contact grouping and copper single mating end single contact grouping |
|   |

Insert Material:

Plastic diallyl phthalate single mating end and glass fiber single mating end

# NSN 5935-01-300-7728

Electrical Plug Connector - Page 2 of 2



### **Contact Surface Treatment Specification:**

Mil-g-45204, type ii, class 2 military specification 1st treatment response single mating end single contact grouping and mil-c-14550, class 2 military specification 2nd treatment response single mating end single contact grouping

### **Terminal Type:**

Solder well single mating end single contact grouping

# **Contact Material Specification:**

Astm-b-140 assn standard single material response single mating end single contact grouping

### **Insert Material Specification:**

Mil-m-14, type gdi-30f military specification all material responses single mating end

# **Included Contact Quantity:**

14 single mating end single contact grouping

## **Included Contact Type:**

Round socket single mating end single contact grouping

### **Precious Material And Location:**

Contact surfaces gold

# **Precious Material And Weight:**

0.014 gold grains, troy

**Precious Material:** 

Gold

# **Thread Series Designator:**

Unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

#### Mil-std (military Standard):

Mil-g-45204 spec.