NSN 5935-01-300-9780

Electrical Receptacle Connector Body - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-300-9780

Thread Class: 2a and 2a **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.492 inches **Overall Diameter:** Between 1.610 inches and 1.641 inches **Environmental Protection:** Moisture proof and salt water resistant and vibration proof and thermal shock resistant and corrosion resistant **Distance From Mounting Shoulder To Front Face:** Between 0.658 inches and 0.707 inches **Mounting Facility Thickness:** Between 0.062 inches and 0.187 inches **Threaded Device Type:** Back shell and mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** 18-11 single mating end **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin Thread Length: 0.290 inches and 0.306 inches Thready Qty Per Inch (tpi): 18 and 18 **Thread Size:** 1.062 inches and 1.250 inches

Shell Material:

Aluminum alloy 6061 or aluminum alloy 380.0 or aluminum alloy a380.0

Shell Surface Treatment:

Cadmium and chromate

Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification all treatment responses

NSN 5935-01-300-9780

Electrical Receptacle Connector Body - Page 2 of 2



Shell Material Specification:

Qq-a-367, t6 federal specification 1st material response or qq-a-591 federal specification 2nd material response or qq-a-591 federal specification 3rd material response

Bushing Accommodation Hole Shape:

Round w/flat

Test Data Document:

81349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

T	'nr	ead	Series	Design	nator:

Unef and unef

Specification Data:

96906-ms3474 government standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-26482 spec.