

View Online at <https://aerobasegroup.com/nsn/5935-01-301-2385>

Thread Class:

2a and 2b

Thread Direction:

Right-hand

Body Style:

Straight shape

Overall Length:

1.050 inches

Overall Height:

0.635 inches

Overall Width:

0.250 inches

Environmental Protection:

Shock resistant and vibration resistant and corrosion resistant and humidity resistant and fungus resistant

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end 1st contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end 1st contact grouping

Polarization Method:

Jackscrew

Connector Locking Method:

Jackscrew-socket

End Application:

Lgm30keyboard

Thready Qty Per Inch (tpi):

56

Thread Size:

0.086 inches

Terminal Location:

Back single mating end 1st contact grouping

Contact Material:

Copper alloy single mating end 1st contact grouping

Contact Surface Treatment:

Gold single mating end 1st contact grouping and nickel single mating end 1st contact grouping

Insert Material:

Plastic polyphenylene single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, cl 1, gr c military specification 1st treatment response single mating end 1st contact grouping and qq-n-290, cl 2 federal specification 2nd treatment response single mating end 1st contact grouping

Criticality Code Justification:

Feat

Terminal Type:

Solder well single mating end 1st contact grouping

Contact Material Specification:

Qq-b-626 federal specification single material response single mating end 1st contact grouping or qq-b-750 federal specification single material response single mating end 1st contact grouping or qq-c-530 federal specification single material response single mating end 1st contact grouping

Insert Material Specification:

Mil-m-24519 military specification single material response single mating end

Included Contact Quantity:

13 single mating end 1st contact grouping

Special Features:

Contact 9 replaced by guide pin

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.013 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Specification Data:

19059-700441 manufacturers source control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.