NSN 5935-01-301-2522

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-301-2522 **Thread Class:** 2a **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 33.66 millimeters **Overall Height:** Between 45.7 millimeters and 46.3 millimeters **Overall Width:** Between 45.7 millimeters and 46.3 millimeters Center To Center Distance Between Mounting Facilities Parallel To Height: Between 34.93 millimeters and 38.10 millimeters Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 34.93 millimeters and 38.10 millimeters **Distance From Mounting Shoulder To Front Face:** 20.1 millimeters **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 23-35 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 116.0 and 160.0 and 191.0 and 311.0 Shell Type: **Connector Locking Method:** Externally threaded shell Thready Qty Per Inch (tpi): 10 **Thread Size:** 37.0 millimeters and 1.625 inches **Thread Pitch In Millimeters:**

1.00

Terminal Location:

Back single mating end single contact grouping

NSN 5935-01-301-2522

Electrical Receptacle Connector - Page 2 of 2



_							
r -	n	+-	rt.	N/I	atα	ria	
·	OI.	ιa	·ι	IVI	alc	ııа	ı .

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic epoxy single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416 federal specification single treatment response

Thread Tolerance Class:

6g external

Included Contact Quantity:

100 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact sufaces gold

Precious Material And Weight:

0.100 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-dod-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Iso m and special acme

Specification Data:

81349-dod-c-38999/20 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

•