

View Online at <https://aerobasegroup.com/nsn/5935-01-302-3245>

Thread Class:

2b and 2b

Thread Direction:

Right-hand and right-hand

Body Style:

Rectangular shape center screwlock

Overall Length:

Between 2.115 inches and 2.135 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 1.740 inches and 1.760 inches

Overall Height:

Between 1.030 inches and 1.090 inches

Overall Width:

Between 0.825 inches and 0.845 inches

Environmental Protection:

Humidity resistant and shock resistant and thermal shock resistant and vibration resistant

Threaded Device Type:

Coupling facility and mounting hole

Mating End Quantity:

1

Contact Position Arrangement Style:

36 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

13.0 single mating end single contact grouping

Polarization Method:

Polarization boss

Connector Locking Method:

Post jacksocket

End Application:

Lan target po

Operating Temperature Rating:

Between -55.0 degrees celsius and 125.0 degrees celsius

Thready Qty Per Inch (tpi):

32 and 40

Thread Size:

0.138 inches and 0.112 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and copper single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end and glass fiber single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type ii, grade c, class 1 military specification 1st treatment response single mating end single contact grouping and mil-c-14550 military specification 2nd treatment response single mating end single contact grouping

Crimping Tool Identifying Number:

04939-tm016it000

Terminal Type:

Pin single mating end single contact grouping

Contact Material Specification:

Qq-b-626, comp ii federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-14, type sgd-f military specification all material responses single mating end

Included Contact Quantity:

36 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.036 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc and unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.