

View Online at <https://aerobasegroup.com/nsn/5935-01-302-3245>

**Thread Class:**

2b and 2b

**Thread Direction:**

Right-hand and right-hand

**Body Style:**

Rectangular shape center screwlock

**Overall Length:**

Between 2.115 inches and 2.135 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 1.740 inches and 1.760 inches

**Overall Height:**

Between 1.030 inches and 1.090 inches

**Overall Width:**

Between 0.825 inches and 0.845 inches

**Environmental Protection:**

Humidity resistant and shock resistant and thermal shock resistant and vibration resistant

**Threaded Device Type:**

Coupling facility and mounting hole

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

36 single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

13.0 single mating end single contact grouping

**Polarization Method:**

Polarization boss

**Connector Locking Method:**

Post jacksocket

**End Application:**

Lan target po

**Operating Temperature Rating:**

Between -55.0 degrees celsius and 125.0 degrees celsius

**Thread Qty Per Inch (tpi):**

32 and 40

**Thread Size:**

0.138 inches and 0.112 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and copper single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end and glass fiber single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type ii, grade c, class 1 military specification 1st treatment response single mating end single contact grouping and mil-c-14550 military specification 2nd treatment response single mating end single contact grouping

**Crimping Tool Identifying Number:**

04939-tm016it000

**Terminal Type:**

Pin single mating end single contact grouping

**Contact Material Specification:**

Qq-b-626, comp ii federal specification single material response single mating end single contact grouping

**Insert Material Specification:**

Mil-m-14, type sgd-f military specification all material responses single mating end

**Included Contact Quantity:**

36 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.036 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Unc and unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.