NSN 5935-01-302-9769

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-302-9769 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Rectangular shape, angle **Overall Length:** 2.170 inches **Overall Height:** 0.518 inches **Overall Width:** 1.198 inches **Environmental Protection:** Thermal shock resistant and shock resistant and vibration resistant and moisture resistant and salt water resistant **Distance Between Mounting Facility Centers:** Between 1.795 inches and 1.805 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 100 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 3.0 single mating end single contact grouping **Polarization Method:** Mating end and jackscrew Shell Type: Solid **Connector Locking Method:** Jackscrew-socket Thready Qty Per Inch (tpi): 56 **Thread Size:** 0.086 inches **Terminal Location:** Side single mating end single contact grouping

Contact Surface Treatment:

Contact Material:

Gold single mating end single contact grouping

Copper alloy single mating end single contact grouping

NSN 5935-01-302-9769

Mil-m-14 spec.

Electrical Receptacle Connector - Page 2 of 2



Insert Material:
Plastic diallyl phthalate glass filled single mating end or plastic polyester single mating end
Terminal Type:
Pin single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Shell Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification all treatment responses
Shell Material Specification:
Qq-a-200 federal specification single material response
Insert Material Specification:
Mil-m-14, ty sdg-f military specification 1st material response single mating end or mil-m-24519 military specification 2nd material response
single mating end
Unable To Decode:
Unable to decode and unable to decode
Included Contact Quantity:
100 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Special Features:
Jackscrew type-female and location-left handandjackscrew type-female and location-right hand
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.100 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):