

View Online at <https://aerobasegroup.com/nsn/5935-01-303-0585>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape w/cover

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.375 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

2.375 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

L24-30 single mating end

Contact Removability:

Nonremovable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

50.0 single mating end all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

125.0 single mating end all contact groupings

Contact Maximum Dc Voltage Rating In Volts:

250.0 single mating end all contact groupings

Polarization Method:

Contact

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Terminal Location:

Side single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Nickel single mating end all contact groupings

Insert Material:

Plastic single mating end

Terminal Type:

Screw single mating end all contact groupings

Shell Material:

Plastic polycarbonate

Included Contact Quantity:

2 single mating end 2nd contact grouping

Included Contact Type:

U-pin single mating end 1st contact grouping

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0