

View Online at <https://aerobasegroup.com/nsn/5935-01-303-0691>

Electrical Insulation Feature:

Uninsulated

Identification Code Color:

Natural

Body Style:

Rivet mounted

Mounting Bushing Length:

Between 0.307 inches and 0.317 inches

Body Length:

Between 0.327 inches and 0.337 inches

Overall Diameter:

Between 0.095 inches and 0.105 inches

Bushing Accommodation Hole Shape:

Round

Accommodated Finger Type:

Test prod single finger

Finger Accommodation Diameter:

0.025 inches single finger and 0.035 inches single finger

Finger Accommodation Length:

0.182 inches single finger and 0.192 inches single finger

Mounting Bushing Diameter:

Between 0.079 inches and 0.089 inches

Bushing Thru-hole Accommodation Diameter:

Between 0.085 inches and 0.087 inches

Mounting Facility Type And Quantity:

1 bushing

Terminal Type:

Printed circuit

Material:

Brass terminal

Material:

Copper alloy terminal

Precious Material And Location:

Contact surface gold

Precious Material:

Gold

Surface Treatment:

Tin and nickel terminal

Surface Treatment:

Gold spring and nickel spring

Test Data Document:

81349-mil-s-83505 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-s-83505/5 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A03400