NSN 5935-01-303-2730

Body Style: Straight shape Overall Length: 3.750 inches

Insert Material Specification:

Mil-m-14, type sdg-f military specification single material response single mating end

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-303-2730

Overall Height:
1.620 inches
Overall Width:
0.540 inches
Environmental Protection:
Shock resistant and vibration resistant and fungus resistant and humidity resistant
Unthreaded Mounting Hole Diameter:
0.080 inches
Distance Between Mounting Facility Centers:
3.500 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
4 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Connector Locking Method:
Friction
Friction
Terminal Location:
Terminal Location:
Terminal Location: Back single mating end single contact grouping
Terminal Location: Back single mating end single contact grouping Contact Material:
Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping
Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment:
Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping and nickel single mating end single contact grouping
Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping and nickel single mating end single contact grouping Insert Material:
Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping and nickel single mating end single contact grouping Insert Material: Plastic diallyl phthalate single mating end
Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping and nickel single mating end single contact grouping Insert Material: Plastic diallyl phthalate single mating end Contact Surface Treatment Specification:
Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping and nickel single mating end single contact grouping Insert Material: Plastic diallyl phthalate single mating end Contact Surface Treatment Specification: Mil-g-45204 military specification 1st treatment response single mating end single contact grouping
Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping and nickel single mating end single contact grouping Insert Material: Plastic diallyl phthalate single mating end Contact Surface Treatment Specification: Mil-g-45204 military specification 1st treatment response single mating end single contact grouping Terminal Type:

NSN 5935-01-303-2730

Electrical Receptacle Connector - Page 2 of 2



Unable To Decode:
Unable to decode and unable to decode
Included Contact Quantity:
122 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.122 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.