

View Online at <https://aerobasegroup.com/nsn/5935-01-303-8487>

**Thread Class:**

2a and 2b

**Thread Direction:**

Right-hand and right-hand

**Body Style:**

Straight shape, internal coupling

**Overall Length:**

2.125 inches

**Overall Diameter:**

1.344 inches

**Environmental Protection:**

Moisture proof and salt water resistant and vibration proof and shock resistant and cold resistant and heat resistant and explosion proof

**Threaded Device Type:**

Back shell and coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

18-1 single mating end

**Contact Removability:**

Removable single mating end all contact groupings

**Contact Maximum Current Rating In Amps:**

22.0 single mating end all contact groupings

**Contact Maximum Ac Voltage Rating In Volts:**

500.0 single mating end 1st contact grouping 200.0 single mating end 2nd contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

700.0 single mating end 1st contact grouping 250.0 single mating end 2nd contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

290.0

**Shell Type:**

Solid

**Connector Locking Method:**

Internally threaded coupling ring

**Operating Temperature Rating:**

Between -55.0 degrees celsius and 200.0 degrees celsius

**Thready Qty Per Inch (tpi):**

18 and 18

**Thread Size:**

1.063 inches and 1.125 inches

**Terminal Location:**

Back single mating end all contact groupings

**Contact Material:**

Copper alloy single mating end all contact groupings

**Contact Surface Treatment:**

Gold single mating end all contact groupings and nickel single mating end all contact groupings

**Insert Material:**

Rubber silicone class q single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, grade c, cl 1 military specification 1st treatment response single mating end all contact groupings and qq-n-290, cl 2 federal specification 2nd treatment response single mating end all contact groupings

**Criticality Code Justification:**

Feat

**Terminal Type:**

Crimp single mating end all contact groupings

**Shell Material:**

Aluminum

**Shell Surface Treatment:**

Cadmium and chromate and nickel

**Shell Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification 1st treatment response and qq-p-416, type 2, cl 3 federal specification 2nd treatment response

**Included Contact Quantity:**

4 single mating end 1st contact grouping 6 single mating end 2nd contact grouping

**Included Contact Type:**

Round pin single mating end all contact groupings

**Special Features:**

16-22 wire size pin contacts in lieu of 16-16

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.010 gold grains, troy

**Precious Material:**

Gold

**Test Data Document:**

81349-mil-c-5015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unef and unef

**Specification Data:**

96906-ms3406 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Mil-std (military Standard):**

Mil-g-45204 spec.