

View Online at <https://aerobasegroup.com/nsn/5935-01-303-9036>

**Body Style:**

Straight shape, internal coupling w/strain relief

**Body Length:**

1.156 inches

**Overall Diameter:**

1.761 inches

**Environmental Protection:**

Moisture resistant and pressure proof

**Cable Entrance Diameter:**

Between 0.365 inches and 0.385 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

40461 single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

7.5 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

500.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

700.0 single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet shell

**Connector Cable Strain Relief Method:**

Cable clamp w/telescoping bushing

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping

**Terminal Type:**

Solder well single mating end single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium

**Shell Surface Treatment Specification:**

Qq-p-416, type 2 federal specification single treatment response

**Included Contact Quantity:**

10 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Special Features:**

Grommet

**Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

**Precious Material:**

Gold and silver

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0