

View Online at <https://aerobasegroup.com/nsn/5935-01-304-1339>

Body Style:

Straight shape

Overall Length:

Between 1.450 inches and 1.470 inches

Overall Height:

1.300 inches

Overall Width:

Between 0.355 inches and 0.365 inches

Body Length:

Between 1.450 inches and 1.470 inches

Unthreaded Mounting Hole Diameter:

0.112 inches

Distance Between Mounting Facility Centers:

Between 1.290 inches and 1.310 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

1.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

300.0 single mating end single contact grouping

Polarization Method:

Mating end

Connector Locking Method:

Latch

End Application:

B52serd513-52

Operating Temperature Rating:

Between -55.0 degrees celsius and 125.0 degrees celsius

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic polyester glass filled single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, gr c, cl 1 military specification single treatment response single mating end single contact grouping

Terminal Type:

Wire wrap single mating end single contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end single contact grouping or qq-b-750 federal specification single material response single mating end single contact grouping or qq-c-533 federal specification single material response single mating end single contact grouping or astm-b-122 assn standard single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-24519, ty gpt-20f or gpt-30f military specification single material response single mating end

Included Contact Quantity:

14 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Special Features:

2 slf tapping 4-24 screws provided

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.014 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-83503 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-c-83503/21 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.