Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-304-4045

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
1.430 inches
Overall Diameter:
1.291 inches
Environmental Protection:
Shock resistant and vibration resistant and fire resistant and moisture resistant
Distance From Mounting Shoulder To Front Face:
0.771 inches
Mounting Facility Thickness:
Between 0.062 inches and 0.125 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
12-dec single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
18.0 and 149.0 and 192.0 and 259.0
Shell Type:
Solid
Features Provided:
Color band engagement indicator
Thready Qty Per Inch (tpi):
20
Thread Size:
0.875 inches
Terminal Location:
Back single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping

NSN 5935-01-304-4045

Electrical Receptacle Connector - Page 2 of 2



Shell Material:

Steel

Shell Surface Treatment:

Passivate

Included Contact Quantity:

12 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Special Features:

Furnished items - grommet

Supplementary Features:

Mounting method - threaded body

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0