NSN 5935-01-304-4343

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-304-4343

Body Style:

Straight shape

Overall Length:

Between 0.949 inches and 0.959 inches

Overall Height:

Between 3.105 inches and 3.115 inches

Overall Width:

Between 1.995 inches and 2.005 inches

Environmental Protection:

Humidity resistant and salt water resistant and shock resistant and thermal shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

Between 0.115 inches and 0.125 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 2.779 inches and 2.787 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 1.428 inches and 1.444 inches

Distance From Mounting Shoulder To Front Face:

Between 0.761 inches and 0.771 inches

Mating End Quantity:

2

Contact Position Arrangement Style:

"106, a106" all mating ends

Contact Removability:

Removable all mating ends single contact grouping

Polarization Method:

3 polarization posts

Shell Type:

Solid

Connector Locking Method:

Friction

Operating Tempurature Rating:

Between -65.0 degrees celsius and 125.0 degrees celsius

Terminal Location:

Back all mating ends single contact grouping

Contact Material:

Copper alloy all mating ends single contact grouping

Contact Surface Treatment:

Gold all mating ends single contact grouping

Insert Material:

Plastic all mating ends

Contact Surface Treatment Specification:

Mil-g-45204, type 1, grade c, class 1 military specification all treatment responses all mating ends single contact grouping

NSN 5935-01-304-4343

Electrical Receptacle Connector - Page 2 of 2



Crimping Tool Identifying Number:
81349-m22520/2-01
Terminal Type:
Crimp single mating end single contact grouping
Guide Design And Location:
Hexagon shape male post right-hand at 12 oclock and hexagon shape male post center at 12 oclock and hexagon shape male post
left-hand at 12 oclock
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Shell Surface Treatment Specification:
Qq-p-416, type 2, class 3 federal specification all treatment responses
Included Contact Quantity:
106 all mating ends single contact grouping
Included Contact Type:
Round pin all mating ends single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.212 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.