NSN 5935-01-304-5812

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-304-5812 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape w/screw locks **Overall Length:** 1.350 inches **Overall Height:** 1.165 inches **Overall Width:** 0.250 inches **Environmental Protection:** Cold resistant and heat resistant and vibration resistant and shock resistant and salt water resistant and humidity resistant and thermal shock **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 2 rows of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Polarization Method:** Jackscrew **Connector Locking Method:** Jackscrew **Operating Tempurature Rating:** Between -65.0 degrees celsius and 125.0 degrees celsius Thready Qty Per Inch (tpi): 56 **Thread Size:** 0.086 inches **Terminal Location:**

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic polyphenylene single mating end

NSN 5935-01-304-5812

Electrical Plug Connector - Page 2 of 2



Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end single contact grouping or qq-c-533 federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-24519 military specification single material response single mating end

Included Contact Quantity:

20 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.020 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.