NSN 5935-01-304-5816

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-304-5816

view Online at https://aerobasegroup.com/hsh/3333-01-304-3010
Body Style:
Straight type
Overall Length:
5.770 inches
Overall Height:
0.453 inches
Overall Width:
Between 0.488 inches and 0.498 inches
Unthreaded Mounting Hole Diameter:
Between 0.135 inches and 0.141 inches
Distance Between Mounting Facility Centers:
5.450 inches
Mating End Quantity:
1
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
3.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
300.0 single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Friction
Operating Tempurature Rating:
Between -55.0 degrees celsius and 105.0 degrees celsius
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic polyamide single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 2, grade c, cl 1 military specification single treatment response single mating end single contact grouping
Terminal Type:
Solder well single mating end single contact grouping
Contact Material Specification:
Qq-c-533 federal specification single material response single mating end single contact grouping

Shell Material:

Aluminum alloy 6061 or aluminum alloy 6063

NSN 5935-01-304-5816

Mil-g-45204 spec.

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Anodize
Shell Surface Treatment Specification:
Mil-a-8625, type 2, cl 2 military specification single treatment response
Shell Material Specification:
Qq-a-200/8 federal specification 1st material response or qq-a-200/9 federal specification 2nd material response
Insert Material Specification:
L-p-410 federal specification single material response single mating end or astm d4066-82 assn standard single material response single
mating end
Included Contact Quantity:
250 single mating end single contact grouping
Included Contact Type:
Square socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.250 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):