Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-304-9542

Thread Class:

2a and 2b

Thread Direction:

Right-hand and left-hand

Body Style:

Straight shape, internal coupling

Overall Length:

1.902 inches

Overall Diameter:

3.156 inches

Environmental Protection:

Waterproof and explosion proof and corrosion resistant and vibration resistant and shock resistant

Threaded Device Type:

Back shell and coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

40-68 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

46.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

117.0

Shell Type:

Solid

Connector Locking Method:

Internally threaded coupling ring

End Application:

5841-01-256-9395 detecting system

Thready Qty Per Inch (tpi):

8 and 16

Thread Size:

2.625 inches and 2.750 inches

Terminal Location:

Back single mating end single contact grouping

NSN 5935-01-304-9542 Electrical Plug Connector - Page 2 of 2



Contact Mate	
	single mating end single contact grouping
Insert Materi	nating end single contact grouping
Rubber single	a maining end
Terminal Typ	eral specification single treatment response single mating end single contact grouping
Solder weil si Shell Materia	ngle mating end single contact grouping
Aluminum allo	
	e Treatment:
Cadmium and	
	ntact Quantity:
	ing end single contact grouping
Included Co	
	ngle mating end single contact grouping
	terial And Location:
Contact surfa	
	terial And Weight:
0.105 silver g	-
Precious Ma	
Silver	
Thread Serie	es Designator:
Un and doubl	e stub
Shelf Life:	
N/a	
Unit Of Meas	sure:
Demilitarizat	ion:
No	
Fiig:	
A039b0	