## NSN 5935-01-304-9542

Electrical Plug Connector - Page 1 of 2



 $\label{thm:com/nsn/5935-01-304-9542} View \ Online \ at \ https://aerobasegroup.com/nsn/5935-01-304-9542$ 

Thread Class:
2a and 2b
Thread Direction:
Right-hand and left-hand
Body Style:
Straight shape, internal coupling
Overall Length:
1.902 inches
Overall Diameter:
3.156 inches
Environmental Protection:
Waterproof and explosion proof and corrosion resistant and vibration resistant and shock resistant
Threaded Device Type:
Back shell and coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
40-68 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
46.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
117.0
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling ring
End Application:
5841-01-256-9395 detecting system
Thready Qty Per Inch (tpi):
8 and 16
Thread Size:
2.625 inches and 2.750 inches
Terminal Location:

Tommar Location

Back single mating end single contact grouping

## NSN 5935-01-304-9542

Fiig: A039b0

Electrical Plug Connector - Page 2 of 2



Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Silver single mating end single contact grouping
Insert Material:
Rubber single mating end
Contact Surface Treatment Specification:
Qq-s-365 federal specification single treatment response single mating end single contact grouping
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and nickel
Included Contact Quantity:
21 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces silver
Precious Material And Weight:
0.105 silver grains, troy
Precious Material:
Silver
Thread Series Designator:
Un and double stub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No