Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-304-9569

Body Style:

Straight shape, w/ or w/o cover

Overall Length:

114.6 millimeters

Center To Center Distance Between Mounting Facilities Parallel To Length:

98.4 millimeters

Overall Height:

146.3 millimeters

Overall Width:

129.7 millimeters

Environmental Protection:

Heat resistant and fire resistant and moisture resistant and cold resistant and watertight

Unthreaded Mounting Hole Diameter:

5.5 millimeters

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

98.4 millimeters

Mating End Quantity:

1

Contact Position Arrangement Style:

4 single mating end

Contact Removability:

Removable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

60.0 single mating end all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

250.0 single mating end all contact groupings

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Lock tab

Operating Tempurature Rating:

Between -40.0 degrees celsius and 80.0 degrees celsius

Features Provided:

Grounded contact

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings



Insert Material:

Plastic polyester single mating end

Terminal Type:

Compression single mating end all contact groupings

Shell Material:

Plastic polyamide

Included Contact Quantity:

3 single mating end 2nd contact grouping

Included Contact Type:

Round socket single mating end all contact groupings

Special Features:

Furnished items - hinged cover plate

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0