

View Online at <https://aerobasegroup.com/nsn/5935-01-305-2933>

**Thread Class:**

2a and 2a and 2a

**Thread Direction:**

Right-hand and right-hand and right-hand

**Body Style:**

Straight shape, external coupling

**Overall Length:**

1.232 inches

**Environmental Protection:**

Vibration resistant and thermal shock resistant and shock resistant and corrosion resistant and moisture resistant

**Threaded Device Type:**

Back shell and coupling facility and mounting bushing

**Mating End Quantity:**

2

**Contact Position Arrangement Style:**

Osm 1st mating end

**Contact Removability:**

Nonremovable all mating ends single contact grouping

**Polarization Method:**

Contact

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded shell

**Width Across Flats:**

0.750 inches

**Thready Qty Per Inch (tpi):**

24 and 36 and 24

**Thread Size:**

0.625 inches and 0.250 inches and 0.625 inches

**Contact Material:**

Copper alloy all mating ends single contact grouping

**Contact Surface Treatment:**

Gold all mating ends single contact grouping

**Insert Material:**

Plastic fluorocarbon all mating ends

**Contact Surface Treatment Specification:**

Mil-g-45204, type 1, grade c military specification single treatment response all mating ends single contact grouping

**Contact Material Specification:**

Qq-c-530 federal specification single material response all mating ends single contact grouping

**Shell Material:**

Stainless steel

**Shell Surface Treatment:**

Passivate

**Shell Material Specification:**

Qq-s-764, class 303 federal specification single material response

**Insert Material Specification:**

Mil-p-19468 military specification single material response all mating ends and mil-p-403 military specification single material response all mating ends

**Included Contact Quantity:**

1 2nd mating end single contact grouping

**Bushing Accommodation Hole Shape:**

Round w/double flat

**Included Contact Type:**

Coaxial socket all mating ends single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.010 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Unef and uns and unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.