## NSN 5935-01-305-2937

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-305-2937

**Body Style:** 

Straight edge type w/mounting flange

**Overall Length:** 

**4.340** inches

**Overall Height:** 

0.670 inches

**Overall Width:** 

0.375 inches

**Unthreaded Mounting Hole Diameter:** 

0.116 inches

**Distance Between Mounting Facility Centers:** 

4.030 inches

**Board Accommodated Length:** 

3.742 inches single board

**Board Accommodated Width:** 

Between 0.055 inches and 0.072 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

2 rows of independent contacts inserted board single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

5.0 single mating end single contact grouping

**Connector Locking Method:** 

Friction

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

**Insert Material:** 

Plastic diallyl phthalate glass filled single mating end

**Contact Surface Treatment Specification:** 

Mil-g-45204, ty ii, class 1 military specification single treatment response single mating end single contact grouping

**Terminal Type:** 

Tab, solder lug single mating end single contact grouping

**Insert Material Specification:** 

Mil-p-19833 military specification single material response single mating end

**Included Contact Quantity:** 

56 single mating end single contact grouping

## NSN 5935-01-305-2937

Electrical Receptacle Connector - Page 2 of 2

single contact grouping



Included Contact Type:
Leaf spring single mating end single
<b>Precious Material And Location:</b>
Contact surfaces gold

**Precious Material And Weight:** 

0.056 gold grains, troy

**Precious Material:** 

Gold

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.