NSN 5935-01-305-2948

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-305-2948 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape, rectangular **Overall Length:** Between 1.570 inches and 1.610 inches **Overall Height:** Between 1.340 inches and 1.360 inches **Overall Width:** Between 2.865 inches and 2.885 inches **Environmental Protection:** Heat resistant **Unthreaded Mounting Hole Diameter:** 0.149 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 0.802 inches and 0.822 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 2.490 inches and 2.510 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 104 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 13.0 single mating end single contact grouping **Polarization Method:** Polarization boss **Connector Locking Method:** Post jacksocket **Operating Tempurature Rating:** Between -54.0 degrees celsius and 125.0 degrees celsius Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches

Terminal Location:

Back single mating end single contact grouping

NSN 5935-01-305-2948

Electrical Receptacle Connector - Page 2 of 2



_							
r -	n	+-	rt.	NЛ	ate	ria	
·	OI.	ιca	·ι	IVI	alc	па	ı .

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, grade c or d class military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Contact Material Specification:

Qq-b-626 federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-14, ty sdg-f military specification single material response single mating end

Included Contact Quantity:

104 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.104 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.