## NSN 5935-01-305-7186



Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-01-305-7186 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** 0.870 inches **Overall Height:** 0.480 inches **Overall Width:** 0.190 inches

**Environmental Protection:** 

Shock resistant and vibration resistant

**Distance Between Mounting Facility Centers:** 

0.656 inches

**Threaded Device Type:** 

Mounting stud

**Mating End Quantity:** 

**Contact Position Arrangement Style:** 

22 single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

**Polarization Method:** 

Guide pin/socket

Thready Qty Per Inch (tpi):

56

Thread Size:

0.086 inches

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

**Insert Material:** 

Plastic diallyl phthalate glass filled single mating end

**Contact Surface Treatment Specification:** 

Mil-g-45204, type ii, class 1 military specification single treatment response single mating end single contact grouping

**Terminal Type:** 

Solder well single mating end single contact grouping

## NSN 5935-01-305-7186

Electrical Receptacle Connector - Page 2 of 2



## **Insert Material Specification:**

Mil-p-19833, type gdi-30 military specification single material response single mating end

**Unable To Decode:** 

Unable to decode and unable to decode

**Included Contact Quantity:** 

9 single mating end single contact grouping

**Included Contact Type:** 

Round pin single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.009 gold grains, troy

**Precious Material:** 

Gold

**Thread Series Designator:** 

Unc

**Shelf Life:** 

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.