# NSN 5935-01-306-0156

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-306-0156

**Body Style:** Straight shape **Overall Length:** 1.200 inches **Environmental Protection:** Vibration resistant and thermal shock resistant and humidity resistant and corrosion resistant **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 1 row of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 2.0 single mating end single contact grouping **Polarization Method:** Mating end **Shell Type:** Solid **Connector Locking Method:** Friction **Operating Tempurature Rating:** Between -65.0 degrees celsius and 125.0 degrees celsius **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic single mating end **Contact Surface Treatment Specification:** Mil-g-45204 military specification single treatment response single mating end single contact grouping **Criticality Code Justification:** Feat **Terminal Type:** Solder well single mating end single contact grouping **Contact Material Specification:** Qq-c-533 federal specification single material response single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Cadmium

# NSN 5935-01-306-0156

Electrical Receptacle Connector - Page 2 of 2



# **Shell Surface Treatment Specification:**

Qq-p-416 federal specification single treatment response

# **Shell Material Specification:**

Qq-a-591 federal specification single material response

# **Included Contact Quantity:**

20 single mating end single contact grouping

# **Included Contact Type:**

Flat socket single mating end single contact grouping

# **Special Features:**

B insert is polarized for b socket insert only

#### **Precious Material And Location:**

Contact surfaces gold

#### **Precious Material And Weight:**

0.020 gold grains, troy

#### **Precious Material:**

Gold

#### Shelf Life:

N/a

#### **Unit Of Measure:**

--

#### **Demilitarization:**

No

# Fiig:

A039b0

# Mil-std (military Standard):

Mil-g-45204 spec.