## NSN 5935-01-306-1401

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-306-1401

Thread Class:

2a and 2a

**Thread Direction:** 

Right-hand and right-hand

**Body Style:** 

Straight shape, external coupling

**Overall Length:** 

1.425 inches

**Overall Diameter:** 

Between 1.360 inches and 1.391 inches

**Distance From Mounting Shoulder To Front Face:** 

Between 0.936 inches and 0.956 inches

**Mounting Facility Thickness:** 

0.300 inches

**Threaded Device Type:** 

Back shell and coupling facility

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

"14-4, 14-04" single mating end

**Contact Removability:** 

Removable single mating end single contact grouping

**Polarization Method:** 

Keyway or multiple keyway

**Insert Position In Deg:** 

0.0

Shell Type:

Solid

**Connector Locking Method:** 

Externally threaded shell

**Thread Size:** 

0.875 inches and 0.937 inches

**Terminal Location:** 

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

**Terminal Type:** 

Crimp single mating end single contact grouping

**Shell Material:** 

Stainless steel

## NSN 5935-01-306-1401

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity
---------------------------

4 single mating end single contact grouping

**Bushing Accommodation Hole Shape:** 

Round w/flat

**Included Contact Type:** 

Round pin single mating end single contact grouping

**Supplementary Features:** 

Mounting method - jam mut

**Thread Series Designator:** 

Unef and unef

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A039b0