

View Online at <https://aerobasegroup.com/nsn/5935-01-306-2389>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

1.625 inches

Overall Height:

Between 1.798 inches and 1.838 inches

Overall Width:

Between 1.798 inches and 1.838 inches

Environmental Protection:

Moisture resistant and corrosion resistant and thermal shock resistant and vibration resistant and heat resistant and cold resistant

Unthreaded Mounting Hole Diameter:

Between 0.142 inches and 0.157 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.392 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.392 inches

Distance From Mounting Shoulder To Front Face:

Between 0.878 inches and 0.898 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

G01 single mating end

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0 and 116.0 and 160.0 and 191.0 and 311.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thread Length:

0.445 inches

Operating Temperature Rating:

Between -55.0 degrees celsius and 200.0 degrees celsius

Thready Qty Per Inch (tpi):

10

Thread Size:

1.625 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic fluorosilicone single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Criticality Code Justification:

Feat

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum

Shell Surface Treatment:

Cadmium and chromate and nickel

Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification 1st treatment response and qq-p-416, type 2, cl 3 federal specification 2nd treatment response

Included Contact Quantity:

92 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Special Features:

20-20 pin contacts in lieu of 20-22

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.092 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-28840 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Double stub

Specification Data:

81349-mil-c-28840/12 government specification

Shelf Life:

Nil

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.