## NSN 5935-01-306-5307

**Body Style:**Straight shape

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-306-5307

Overall Length:
1.531 inches
Overall Height:
0.622 inches
Overall Width:
0.492 inches
Unthreaded Mounting Hole Diameter:
0.125 inches
Distance Between Mounting Facility Centers:
1.311 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
15 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
1.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
25.0 single mating end single contact grouping
Polarization Method:
Mating end
Shell Type:
Solid
Connector Locking Method:
Friction
Connector Cable Strain Relief Method:
Bracket
Operating Tempurature Rating:
Between -25.0 degrees celsius and 105.0 degrees celsius
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Glass single mating end and plastic polycarbonate single mating end
Terminal Type:
Insulation piercing single mating end single contact grouping

## NSN 5935-01-306-5307

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Metal
Included Contact Quantity:
15 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.015 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
<del>.</del>
Demilitarization:
No
Fiig:
A039b0