Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-306-5322

#### **Body Style:**

Rectangular shape, insulation piercing

### **Overall Length:**

Between 2.714 inches and 2.744 inches

## **Overall Height:**

0.886 inches

**Overall Width:** 

0.509 inches

#### **Unthreaded Mounting Hole Diameter:**

#### Between 0.146 inches and 0.156 inches

### **Distance Between Mounting Facility Centers:**

2.500 inches

### Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

37 single mating end

## Contact Removability:

Removable single mating end single contact grouping

#### **Polarization Method:**

Mating end

# Shell Type:

Solid

### **Connector Locking Method:**

Friction

### Terminal Location:

Back single mating end single contact grouping

### **Contact Material:**

Copper alloy single mating end single contact grouping

# Contact Surface Treatment:

Gold and nickel single mating end single contact grouping

## **Insert Material:**

Plastic single mating end

# Contact Surface Treatment Specification:

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping

# **Terminal Type:**

Insulation piercing single mating end single contact grouping

## Shell Material:

Steel

# Shell Surface Treatment:

Tin

### **Included Contact Quantity:**

37 single mating end single contact grouping



## Included Contact Type:

Round socket single mating end single contact grouping

Color:

Black

**Precious Material And Location:** 

Contact surfaces gold

Precious Material And Weight:

0.037 gold grains, troy

**Precious Material:** 

Gold

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.