

View Online at <https://aerobasegroup.com/nsn/5935-01-306-6659>

Body Style:

Straight type

Overall Length:

1.610 inches

Overall Height:

0.710 inches

Overall Width:

0.630 inches

Environmental Protection:

Humidity resistant and vibration resistant and shock resistant

Unthreaded Mounting Hole Diameter:

0.136 inches

Distance Between Mounting Facility Centers:

1.150 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

12 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

750.0 single mating end single contact grouping

Polarization Method:

Mating end

Connector Locking Method:

Latch

End Application:

6625-01-255-4547 voltmeter

Operating Temperature Rating:

Between -55.0 degrees celsius and 105.0 degrees celsius

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic polyamide single mating end

Criticality Code Justification:

Feat

Terminal Type:

Pin single mating end single contact grouping

Insert Material Specification:

Mil-m-20693a military specification single material response single mating end

Included Contact Quantity:

12 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Special Features:

Item supplied with offset mounting ears

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.012 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-m-20693a spec.