## NSN 5935-01-306-7006

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-306-7006 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.662 inches **Overall Height:** 1.375 inches **Overall Width:** 1.375 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.188 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.188 inches **Distance From Mounting Shoulder To Front Face:** 0.750 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 18-11 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: **Connector Locking Method:** Externally threaded shell **End Application:** An/sqq-8 (v) 6 unit 132 **Thread Size:** 1.0625 inches **Terminal Location:** 

Back single mating end single contact grouping

**Insert Material:** 

Silicon single mating end

## NSN 5935-01-306-7006

Electrical Receptacle Connector - Page 2 of 2



| Terminal Type:  |
|---|
| Crimp single mating end single contact grouping                           |
| Shell Material:   |
| Aluminum alloy  |
| Shell Surface Treatment:  |
| Cadmium   |
| Shell Surface Treatment Specification:                                    |
| Qq-p-416, type 2, class 3 federal specification single treatment response |
| Included Contact Quantity:  |
| 5 single mating end single contact grouping                               |
| Included Contact Type:  |
| Round pin single mating end single contact grouping                       |
| Thread Series Designator:   |
| Unef  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A039b0  |