# NSN 5935-01-306-9613

Electrical Receptacle Connector - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5935-01-306-9613 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** 1.880 inches **Overall Height:** Between 1.146 inches and 1.170 inches **Overall Width:** Between 3.000 inches and 3.030 inches **Environmental Protection:** Humidity resistant and shock resistant and thermal shock resistant and corrosion resistant and vibration resistant Center To Center Distance Between Mounting Facilities Parallel To Height: Between 0.558 inches and 0.566 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 2.570 inches and 2.580 inches **Distance From Mounting Shoulder To Front Face:** Between 0.615 inches and 0.630 inches **Threaded Device Type:** Mounting hole **Mating End Quantity: Contact Position Arrangement Style:** 32 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Mating end and guide pin/socket Shell Type: **Connector Locking Method:** Friction **Operating Tempurature Rating:** Between -65.0 degrees celsius and 200.0 degrees celsius Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.138 inches

**Terminal Location:** 

Back single mating end single contact grouping

# NSN 5935-01-306-9613

Electrical Receptacle Connector - Page 2 of 3



_					-		
r -	n	+-	rt.	NЛ	210	ria	
·	OI.	ιca	·ι	IVI	alc	ı ıa	ı .

Copper alloy single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping

# **Contact Surface Treatment Specification:**

Mil-g-45204, type 2, grade c, cl 1 military specification single treatment response single mating end single contact grouping

# **Terminal Type:**

Crimp single mating end single contact grouping

#### **Shell Material:**

Aluminum alloy

#### **Shell Surface Treatment:**

Nickel

#### **Shell Surface Treatment Specification:**

Mil-c-26074, grade a, cl 3 or 4 military specification single treatment response

#### **Shell Material Specification:**

Qq-a-591 federal specification single material response

#### **Unable To Decode:**

Unable to decode and unable to decode

# **Included Contact Quantity:**

32 single mating end single contact grouping

# **Included Contact Type:**

Round socket single mating end single contact grouping

# **Special Features:**

Furnished items - spare contact

# **Precious Material And Location:**

Contact surfaces gold

# **Precious Material And Weight:**

0.032 gold grains, troy

# **Precious Material:**

Gold

# **Supplementary Features:**

Mounting method - spring

# **Test Data Document:**

81349-mil-c-83733 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# **Thread Series Designator:**

Unc

# **Specification Data:**

81349-mil-c-83733/7 government specification

# Shelf Life:

N/a

### **Unit Of Measure:**

--

**Demilitarization:** 

# NSN 5935-01-306-9613

Electrical Receptacle Connector - Page 3 of 3



Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.