## NSN 5935-01-307-7577

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-307-7577

Thread Class:
2a and 2b
Thread Direction:
Right-hand and right-hand
Body Style:
Angle shape, w/o cable clamp
Overall Diameter:
1.156 inches
Body Angle In Deg:
90.0
Environmental Protection:
Moisture proof and salt water resistant and vibration proof and cold resistant and heat resistant and thermal shock resistant and shock
resistant
Threaded Device Type:
Back shell and coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
3 number 16 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
22.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling ring
End Application:
1010-01-233-9493 upgunned wpns station
Distance From Centerline To Connector End:
1.937 inches
Distance From Centerline To Cable End:

20 and 20

1.594 inches

Thready Qty Per Inch (tpi):

## **NSN 5935-01-307-7577**Electrical Plug Connector - Page 2 of 2



Thread Size:
0.750 inches and 0.875 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Silver single mating end single contact grouping
Insert Material:
Rubber single mating end or rubber silicone class q single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Anodize
Included Contact Quantity:
3 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces silver
Precious Material And Weight:
0.003 silver grains, troy
Precious Material:
Silver
Thread Series Designator:
Unef and unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0