

View Online at <https://aerobasegroup.com/nsn/5935-01-307-9209>

Body Style:

Straight shape

Overall Length:

Between 1.295 inches and 1.305 inches

Overall Height:

0.475 inches

Overall Width:

0.115 inches

Environmental Protection:

Thermal shock resistant and shock resistant and vibration resistant and moisture resistant and salt water resistant

Mating End Quantity:

1

Contact Position Arrangement Style:

1 row of contacts non-inserted board single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Polarization Method:

Guide pin/socket

Connector Locking Method:

Friction

End Application:

6625-01-152-6705 test set, transponder set

Operating Temperature Rating:

Between -55.0 degrees celsius and 85.0 degrees celsius

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic polyamide single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, cl 0 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Included Contact Quantity:

16 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Special Features:

Round guide socket located between contacts 15 and 16

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.016 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.