

View Online at <https://aerobasegroup.com/nsn/5935-01-307-9210>

**Thread Class:**

2a and 2b and 2a

**Thread Direction:**

Right-hand and right-hand and right-hand

**Body Style:**

Straight shape

**Overall Length:**

Between 0.872 inches and 0.878 inches

**Overall Height:**

Between 0.480 inches and 0.520 inches

**Overall Width:**

Between 0.190 inches and 0.230 inches

**Environmental Protection:**

Humidity resistant and shock resistant and thermal shock resistant and vibration resistant

**Distance Between Mounting Facility Centers:**

Between 0.641 inches and 0.671 inches

**Threaded Device Type:**

Coupling facility and mounting stud

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

20-sep single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Polarization Method:**

Jackscrew

**Connector Locking Method:**

Jackscrew-socket

**End Application:**

Countermeasures set, an/alq-172

**Operating Temperature Rating:**

Between -55.0 degrees celsius and 125.0 degrees celsius

**Thready Qty Per Inch (tpi):**

56 and 56 and 56

**Thread Size:**

0.086 inches and 0.086 inches and 0.086 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate glass filled single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, grade c, class 1 military specification single treatment response single mating end single contact grouping

**Crimping Tool Identifying Number:**

14933-m22520/2-01

**Terminal Type:**

Crimp single mating end single contact grouping

**Contact Material Specification:**

Qq-c-530 federal specification single material response single mating end single contact grouping or qq-c-533 federal specification single material response single mating end single contact grouping

**Insert Material Specification:**

Mil-m-14, type sgd-f military specification single material response single mating end or mil-p-19833, type gdi-30f military specification single material response single mating end

**Unable To Decode:**

Unable to decode and unable to decode

**Included Contact Quantity:**

9 single mating end single contact grouping

**Included Contact Type:**

Round socket single mating end single contact grouping

**Special Features:**

Jackscrew type-male and location-left hand and jackscrew type-female and location-right hand

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.009 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Unc and unc and unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.