

View Online at <https://aerobasegroup.com/nsn/5935-01-308-2065>

**Body Style:**

Straight type

**Overall Length:**

Between 3.730 inches and 3.750 inches

**Overall Height:**

Between 0.545 inches and 0.565 inches

**Overall Width:**

Between 0.407 inches and 0.427 inches

**Environmental Protection:**

Shock resistant and vibration resistant and corrosion resistant

**Unthreaded Mounting Hole Diameter:**

Between 0.100 inches and 0.120 inches

**Distance Between Mounting Facility Centers:**

Between 3.530 inches and 3.550 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

3 rows of contacts non-inserted board single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

3.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

300.0 single mating end single contact grouping

**Polarization Method:**

Mating end

**Connector Locking Method:**

Friction

**Operating Temperature Rating:**

Between -55.0 degrees celsius and 125.0 degrees celsius

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic polyester glass filled single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Pin single mating end single contact grouping

**Included Contact Quantity:**

96 single mating end single contact grouping

**Included Contact Type:**

Brush socket single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.096 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.