NSN 5935-01-308-5069

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-308-5069

view Offiline at https://defobasegroup.com/hsh/0500-01-000-0005
Body Style:
Straight shape, external coupling
Overall Length:
1.220 inches
Overall Height:
1.705 inches
Overall Width:
1.705 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.304 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.304 inches
Distance From Mounting Shoulder To Front Face:
0.540 inches
Mating End Quantity:
1
Contact Removability:
Removable single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Detent
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 1, cl 00 military specification 1st treatment response single mating end single contact grouping
Crimping Tool Identifying Number:
71468-cct-2016-1
Terminal Type:
Crimp single mating end single contact grouping
Contact Material Specification:
Astm b21 assn standard single material response single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:

Anodize

NSN 5935-01-308-5069

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment Specification:

Qq-a-5625 federal specification single treatment response

Shell Material Specification:

Qq-a-225 federal specification single material response

Insert Material Specification:

Mil-m-14, ty mdg military specification single material response single mating end

Included Contact Quantity:

33 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Special Features:

Nitrogen transfer pin located in position 35; relief fitting and stainless steel tubing supplied with connector

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.033 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.