Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-308-6311

view Online at https://aeiobasegroup.com/hsi//3933-01-300-0311
Body Style:
Straight shape
Overall Length:
1.100 inches
Overall Height:
0.560 inches
Overall Width:
0.250 inches
Environmental Protection:
Heat resistant and cold resistant
Mating End Quantity:
1
Contact Position Arrangement Style:
1 row of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
3.5 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
250.0 single mating end single contact grouping
Connector Locking Method:
Friction
-
Friction
Friction Operating Tempurature Rating:
Friction Operating Tempurature Rating: Between -40.0 degrees celsius and 105.0 degrees celsius
Friction Operating Tempurature Rating: Between -40.0 degrees celsius and 105.0 degrees celsius Terminal Location:
Friction Operating Tempurature Rating: Between -40.0 degrees celsius and 105.0 degrees celsius Terminal Location: Back single mating end single contact grouping
Friction Operating Tempurature Rating: Between -40.0 degrees celsius and 105.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material:
Friction Operating Tempurature Rating: Between -40.0 degrees celsius and 105.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping
Friction Operating Tempurature Rating: Between -40.0 degrees celsius and 105.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment:
Friction Operating Tempurature Rating: Between -40.0 degrees celsius and 105.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Tin single mating end single contact grouping
Friction Operating Tempurature Rating: Between -40.0 degrees celsius and 105.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Tin single mating end single contact grouping Insert Material:
 Friction Operating Tempurature Rating: Between -40.0 degrees celsius and 105.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Tin single mating end single contact grouping Insert Material: Plastic polyamide single mating end
 Friction Operating Tempurature Rating: Between -40.0 degrees celsius and 105.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Tin single mating end single contact grouping Insert Material: Plastic polyamide single mating end Terminal Type:
 Friction Operating Tempurature Rating: Between -40.0 degrees celsius and 105.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Tin single mating end single contact grouping Insert Material: Plastic polyamide single mating end Terminal Type: Pin single mating end single contact grouping
 Friction Operating Tempurature Rating: Between -40.0 degrees celsius and 105.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Tin single mating end single contact grouping Insert Material: Plastic polyamide single mating end Terminal Type: Pin single mating end single contact grouping Included Contact Quantity:
 Friction Operating Tempurature Rating: Between -40.0 degrees celsius and 105.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Tin single mating end single contact grouping Insert Material: Plastic polyamide single mating end Terminal Type: Pin single mating end single contact grouping Included Contact Quantity: 11 single mating end single contact grouping
 Friction Operating Tempurature Rating: Between -40.0 degrees celsius and 105.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Tin single mating end single contact grouping Insert Material: Plastic polyamide single mating end Terminal Type: Pin single mating end single contact grouping Included Contact Quantity: 11 single mating end single contact grouping
Friction Operating Tempurature Rating: Between -40.0 degrees celsius and 105.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Tin single mating end single contact grouping Insert Material: Plastic polyamide single mating end Plastic polyamide single contact grouping Minerial Type: Pin single mating end single contact grouping Included Contact Quantity: 11 single mating end single contact grouping Square pin single mating end single contact grouping



Demilitarization:

No

Fiig:

A039b0