
Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-309-0032

Thread Class:	
2b	
Body Style:	
Straight shape, inte	rnal coupling
Overall Length:	
0.884 inches	
Overall Width:	
1.234 inches	
Distance Between	Centerlines Of Mounting Facilities Parallel To Body Width:
0.969 inches	
Threaded Device 1	ype:
Coupling facility	
Contact Position A	rrangement Style:
16-8 single mating	nd
Contact Maximum	Current Rating In Amps:
22.0 single mating e	nd single contact grouping
Contact Maximum	Ac Voltage Rating In Volts:
900.0 single mating	end single contact grouping
Contact Maximum	Dc Voltage Rating In Volts:
1250.0 single matin	g end single contact grouping
Shell Type:	
Solid	
Connector Locking	Method:
Bayonet shell	
Thread Size:	
1.000 inches	
Terminal Type:	
Crimp single mating	end single contact grouping
Included Contact	luantity:
8 single mating end	single contact grouping
Included Contact	ype:
Round socket single	mating end single contact grouping
Supplementary Fe	atures:
Mounting method -	lange
Test Data Docume	nt:
81349-mil-c-38999	pecification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes co	mmercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and	erformance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Des	gnator:
Unef	
Shelf Life:	
N/a	
Unit Of Measure:	



Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-38999 spec.