## NSN 5935-01-309-0032



Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-01-309-0032 **Thread Class:** 2b **Body Style:** Straight shape, internal coupling **Overall Length:** 0.884 inches **Overall Width:** 1.234 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.969 inches **Threaded Device Type:** Coupling facility **Contact Position Arrangement Style:** 16-8 single mating end **Contact Maximum Current Rating In Amps:** 22.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 900.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 1250.0 single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Bayonet shell **Thread Size:** 1.000 inches **Terminal Type:** Crimp single mating end single contact grouping **Included Contact Quantity:** 8 single mating end single contact grouping **Included Contact Type:** Round socket single mating end single contact grouping **Supplementary Features:** Mounting method - flange **Test Data Document:** 81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Thread Series Designator:** Unef

--

N/a

Shelf Life:

**Unit Of Measure:** 

## NSN 5935-01-309-0032

Electrical Receptacle Connector - Page 2 of 2



Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-38999 spec.