## NSN 5935-01-309-3371

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-309-3371

Body Style:

Straight type

**Overall Length:** 

Between 3.360 inches and 3.390 inches

**Overall Width:** 

0.330 inches

**Body Height:** 

0.437 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

2 rows of contacts non-inserted board single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

3.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:** 

600.0 single mating end single contact grouping

**Connector Locking Method:** 

Friction

**End Application:** 

6625-01-016-5966 gain phase meter

**Operating Tempurature Rating:** 

Between -55.0 degrees celsius and 150.0 degrees celsius

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:** 

Plastic diallyl phthalate single mating end

**Contact Surface Treatment Specification:** 

Mil-g-45204, type 2 military specification 1st treatment response single mating end single contact grouping

**Terminal Type:** 

Solder well single mating end single contact grouping

**Insert Material Specification:** 

Mil-m-14 military specification single material response single mating end

**Included Contact Quantity:** 

50 single mating end single contact grouping

**Included Contact Type:** 

Square socket single mating end single contact grouping

## NSN 5935-01-309-3371

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location:
Contact surfaces gold
<b>Precious Material And Weight:</b>
0.050 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-g-45204 spec.