## NSN 5935-01-309-5515

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-309-5515 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 0.994 inches **Overall Height:** 1.578 inches **Overall Width:** 1.578 inches **Environmental Protection:** Corrosion resistant and shock resistant and vibration proof **Unthreaded Mounting Hole Diameter:** 0.125 inches **Center To Center Distance Between Mounting Facilities Parallel To Height:** 1.250 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.250 inches **Distance From Mounting Shoulder To Front Face:** 0.447 inches **Threaded Device Type:** Back shell **Mating End Quantity: Contact Position Arrangement Style:** 22-35 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 100.0 Shell Type: Solid Thready Qty Per Inch (tpi): 18 **Thread Size:** 1.312 inches

**Terminal Location:** 

Back single mating end single contact grouping

## NSN 5935-01-309-5515

Electrical Receptacle Connector - Page 2 of 2



## **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic single mating end **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:** Aluminum alloy **Included Contact Quantity:** 100 single mating end single contact grouping **Included Contact Type:** Round socket single mating end single contact grouping **Precious Material:** Gold **Supplementary Features:** Mounting method - unthreaded hole **Thread Series Designator:** Unef Shelf Life: N/a **Unit Of Measure:** Demilitarization: No Fiig:

A039b0