NSN 5935-01-310-1922

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-310-1922

Body Style:

Straight shape

Overall Length:

Between 1.410 inches and 1.450 inches

Overall Height:

Between 0.490 inches and 0.550 inches

Overall Width:

Between 0.350 inches and 0.390 inches

Environmental Protection:

Vibration resistant and corrosion resistant and shock resistant and humidity resistant

Mating End Quantity:

4

Contact Position Arrangement Style:

3 rows of contacts non-inserted board single mating end

Contact Removability:

Removable single mating end 1st contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end 1st contact grouping

Polarization Method:

Guide pin/socket

Connector Locking Method:

Friction

Operating Tempurature Rating:

Between -55.0 degrees celsius and 125.0 degrees celsius

Terminal Location:

Back single mating end 1st contact grouping

Contact Material:

Copper alloy single mating end 1st contact grouping

Contact Surface Treatment:

Gold single mating end 1st contact grouping and nickel single mating end 1st contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type ii, grade c military specification 1st treatment response single mating end 1st contact grouping and qq-n-290 federal specification 2nd treatment response single mating end 1st contact grouping

Terminal Type:

Pin single mating end 1st contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end 1st contact grouping

Insert Material Specification:

Mil-m-14, type sdg-f military specification single material response single mating end

Unable To Decode:

Unable to decode and unable to decode

NSN 5935-01-310-1922

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity: 39 single mating end 1st contact grouping **Included Contact Type:** Round pin single mating end 1st contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.039 gold grains, troy **Precious Material:** Gold Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.